

# 伺服电机参数

型号	法兰尺寸	额定功率 (W)	额定转矩 (Nm)	最大转矩 (Nm)	额定电流 (Arms)	额定转速 (rpm)	最高转速 (rpm)	转子转动惯量 (kg.m <sup>2</sup> ×10 <sup>-4</sup> )	电压 (V)
EAM-WH-A530A-□3▲	40	50	0.16	0.48	0.6	3000	6000	0.035 (0.038)	220
EAM-WH-0130A-□3▲	40	100	0.32	0.96	1	3000	6000	0.053 (0.056)	220
EAM-WH-0230A-□3▲	60	200	0.64	1.92	1.4	3000	6000	0.29 (0.32)	220
EAM-WH-0430A-□3▲	60	400	1.27	3.81	2.8	3000	6000	0.53 (0.56)	220
EAM-WH-0830A-□3▲	80	750	2.4	7.2	3.8	3000	6000	1.62 (1.72)	220
EAM-WH-1030A-□3▲	80	1000	3.2	9.6	5.5	3000	6000	2.1 (2.2)	220
EAM-WG-1230A-□3▲	110	1200	4	12	5	3000	3500	7.3 (7.4)	220
EAM-WH-1530A-□3▲	110	1500	5	15	6	3000	3500	9.2 (9.3)	220
EAM-WH-1830A-□3▲	110	1800	6	18	7.7	3000	3500	10.8 (10.9)	220
EAM-WG-0915A-□3▲	130	850	5.39	16.17	6.9	1500	3000	10.9 (12.13)	220
EAM-WG-1315A-□3▲	130	1300	8.34	25.02	10.7	1500	3000	16.9 (18.13)	220
EAM-WG-1815A-□3▲	130	1800	11.5	28.7	13.8	1500	3000	21.4 (22.63)	220
EAM-WG-0915T-□3▲	130	850	5.39	16.17	4	1500	3000	10.9 (12.13)	380
EAM-WG-1315T-□3▲	130	1300	8.34	25.02	6	1500	3000	16.9 (18.13)	380
EAM-WG-1815T-□3▲	130	1800	11.5	34.5	8.5	1500	3000	21.4 (22.63)	380
EAM-WG-3030T-□3▲	130	3000	10	23	8	3000	3500	25.5 (27)	380
EAM-WG-2915T-□3▲	180	2900	18.6	55.8	11.9	1500	3000	62.5 (69.5)	380
EAM-WH-4415T-□3▲	180	4400	28.4	85.2	16.5	1500	3000	88.5 (94.5)	380
EAM-WH-5515T-□3▲	180	5500	35	105	20.8	1500	3000	114.4 (120.4)	380
EAM-WH-7515T-□3▲	180	7500	48	120	26	1500	3000	136.6 (142.6)	380

备注：

当□是U：支持23位光学编码器，需配合FV5-R3驱动器

当□是3：支持17位磁性编码器，需配合FV5-R1驱动器

当▲是0：电机不带抱闸

当▲是2：电机带抱闸

转动惯量括号内为带抱闸电机数据